

# VisiDipper

The VisiDipper is the most innovative design for ice cream dipping cabinets in over 25 years.

VisiDipper provides 75% more product viewing area than standard canopy dipping cabinets and features a unique air piston-assisted, tempered, scratch-proof service-side lid for no-hands easy opening.

The VisiDipper product line features both straight and curved glass models in 4-can, 8-can, 12-can, and 16-can models.



## FEATURES:

- New refrigerant/compressor design
- Microprocessor digital controller with LED digital display
- 4½" lower front glass offers 75% more product viewing area
- Improved energy efficiency, reliability and quieter operation
- Stainless-steel top service area
- Slide-out condensing unit for easy maintenance and serviceability
- Additional storage capacity underneath product display level

- Energy Star compliant
- Temperature range 10°F to -15°F
- Durable powder-coat paint finish interior and exterior
- 8-foot 15A power cord with NEMA 5-15 plug
- Manual defrost

## OPTIONAL ACCESSORIES:

- Can skirt kits
- Caster kits
- Dipperwell
- Gelato pan racks (pans not included)
- Frost shield kits
- Leg kits

formerly  
**Kelvinator** 

Project:

Quantity:

Item#:

Model Specified:


Approval: \_\_\_\_\_

# KDC-V/CKDC-V VisiDipper Ice Cream Dipping Cabinets





## TECHNICAL DATA

MODEL	KDC/CKDC27V	KDC/CKDC47V	KDC/CKDC67V	KDC/CKDC87V
Temp Range	+10°F to -15°F	+10°F to -15°F	+10°F to -15°F	+10°F to -15°F
<b>Exterior Dimensions</b>				
Length	25.75	46.5"	67"	88"
Depth	26.75	26.75"	26.75"	26.75"
Height	51.81	51.81"	51.81"	51.81"
<b>Capacity</b>	4.6 cu. ft.	12.0 cu. ft.	19.1 cu. ft.	26.4 cu. ft.
<b>Capacity</b> (3-gal. tubs)	4	12	20	28
<b>Facings</b> (3-gal. tubs)	4	8	12	16
<b>Storage</b> (3-gal. tubs)	0	4	8	12
<b>Compressor</b>	Hermetic	Hermetic	Hermetic	Hermetic
<b>Shipping Weight</b>	235 lbs.	365 lbs.	525 lbs.	635 lbs.
<b>Condensor Type</b>	Bare Tube	Bare Tube	Bare Tube	Bare Tube
<b>Lighting</b>	LED	LED	LED	LED
<b>Electrical</b>	115/60/1	115/60/1	115/60/1	115/60/1
<b>Rated Amps</b>	11.0	11.5	12.5	12.5

STRAIGHT GLASS  
SIDE VIEW



CURVED GLASS  
SIDE VIEW




## SPECIFICATIONS

Item: \_\_\_\_\_ KDC \_\_\_\_\_ V

Furnish ( ) quantity. VisiDipper Ice Cream Dipping Cabinets, Kelvinator model \_\_\_\_\_ KDC \_\_\_\_\_ V. The unit construction shall consist of a 20-ga. white powder-coat finished galvanized steel interior and exterior, foamed in place. The unit will be supplied with an air piston-assisted, tempered, scratch-proof service-side lid and a stainless-steel top service area.

Cabinet as specified to use R-404a refrigerant. Refrigeration control shall be thermostatic control with a temperature range of 10°F to -15°F. Cabinet to have independent on/off switch for compressor and light switch to be mounted in the shell of the cabinet and to be furnished with a drain connection. Cabinet to be provided as a rear-air intake and front-air discharge (consult factory for rear-air intake and discharge).

### ELECTRICAL CONNECTION



Global Refrigeration, Inc., reserves the right to change specifications, terms, and prices without notice.

5855 Grant Avenue, Cleveland, OH 44105

888.650.9799

www.globalref.com