



Item No. _____

ISI-161TI

Soft Serve Freezer

Single Flavor

Icetro by Taylor compact Single Flavor, Gravity Fed, Hopper Agitator.

Features

Offer all the popular soft serve variations, from low-fat to non-fat ice creams or yogurt.

Freezing Cylinder

One, 1.5 quart (1.4 liter).

Mix Hopper

One, 3.2-quart (3-liter) separate hopper refrigeration (SHR) maintains the mix below 41°F (5°C) in both Auto and Standby modes.

Indicator Lights

The Mix Low and Mix Out indicators alert the operator to add more mix. An audible alarm can be activated to sound when the mix is running low. If the Mix Out indicator is illuminated, the unit will automatically shut down to prevent any damage.


Electronic Controls

Microprocessor touch controls are integrated. Temperatures in the hopper and freezing cylinder are displayed at any point during operation. The microprocessor maintains a creamy consistency without dispensing soft serve for up to two hours.

Standby

During long no-use periods, the Standby feature maintains safe product temperatures in the mix hopper and freezing cylinder.

ISI-161TI ISI-161TI2D327



FIGURES IN BRACKETS INDICATE MILLIMETERS / DECIMAL AND FRACTIONAL DIMENSIONS EQUAL TO (PLUS OR MINUS 1/16 INCH [1.5mm]).

Weights	lbs.	kgs.
Net	196	89
Crated	238	108

**For reference only*

	cu. ft.	cu. m.
Volume	17.75	0.50
Dimensions	in.	mm.
Width	11.8	300
Depth	30.5	775.9
Height	31.6	802

** Designed to rest on a plastic pad directly on counter top.*

Electrical	Total Ampacity	Supplied NEMA Cord
115/60/1	13.2	NEMA 5-20p

Specifications

Electrical

One dedicated electrical connection is required. Refer to the electrical chart for the proper electrical requirements. It is designed to be connected using a cord and plug.

Beater Motor

One, 0.5 HP.

Refrigeration System

Main system, one 2,163 BTU/Hr using R404A. The main system covers Separate Hopper Refrigeration. (BTUs may vary based on application.)

BTU/hr

2,163 BTU/Hr using R404A.

Air Cooled

Minimum 7.9 in. (200 mm) on the left side, and 19.7 (500 mm) on the right and rear sides to prevent recirculation of warm air. Minimum air clearances must be met to ensure adequate airflow for optimum performance.

This unit may be manufactured with other electrical characteristics and may have additional regulatory agency approvals. Consult the local Taylor distributor for other electrical characteristics and agency approvals based on specific electrical and country requirements.

(For exact electrical information, approval marks, and refrigerant, always refer to the data label of the unit.)

Continuing research results in steady improvements; therefore, these specifications are subject to change without notice.

Bidding Specs

Electrical: Volt _____ Hz _____ ph _____

Neutral: ☐Yes ☐No Cooling: ☐Air ☐Water ☐NA

Options: _____

All options may not be available in combination with others or with all electrical or cooling configurations. Please consult your local Taylor Distributor.

Authorized Taylor Distributor

TAYLOR®
750 N. Blackhawk Blvd.
Rockton, Illinois 61072
www.taylor-company.com